

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

---

### SECTION 1. IDENTIFICATION

Trade name : TBPA-50-AL1

**Manufacturer or supplier's details**

Company name of supplier : United Initiators, Inc.

Address : 555 Garden Street  
Elyria OH 44035 USA

Telephone : +1-440-323-3112

Telefax : +1-440-323-2659

Emergency telephone : CHEMTREC US (24h): +1-800-424-9300  
CHEMTREC WORLD (24h): +1-703-527-3887

E-mail address of person  
responsible for the SDS : cs-initiators.nafta@united-in.com

**Recommended use of the chemical and restrictions on use**

Recommended use : polymerization initiators

---

### SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 3

Organic peroxides : Type C

Acute toxicity (Inhalation) : Category 3

Eye irritation : Category 2A

Skin sensitization : Category 1

Aspiration hazard : Category 1

Short-term (acute) aquatic  
hazard : Category 2

Long-term (chronic) aquatic  
hazard : Category 2

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |                                |                                 |
|----------------|------------------------------|----------------------------|--------------------------------|---------------------------------|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020 | Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|--------------------------------|---------------------------------|

### GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.  
H242 Heating may cause a fire.  
H304 May be fatal if swallowed and enters airways.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.  
P233 Keep container tightly closed.  
P234 Keep only in original container.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing mist or vapors.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P331 Do NOT induce vomiting.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

Version 2.1      Revision Date: 04/24/2024      SDS Number: 60000000061      Date of last issue: 03/27/2020  
Date of first issue: 04/03/2019

---

attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P391 Collect spillage.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 Protect from sunlight.

P411 + P235 Store at temperatures not exceeding 104 °F/ 40 °C. Keep cool.

P420 Store away from other materials.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Organic Peroxide  
Liquid mixture

### Components

| Chemical name   | CAS-No.                  | Concentration (% w/w) |
|---|--------------------------|-----------------------|
| tert-butyl peracetate   | 107-71-1                 | >= 45 - < 50          |
| Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9) | 64742-48-9<br>68551-19-9 | >= 45 - < 50          |

Actual concentration is withheld as a trade secret

---

## SECTION 4. FIRST AID MEASURES

General advice : Take off contaminated clothing and shoes immediately.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Call a physician immediately.  
Never give anything by mouth to an unconscious person.  
If unconscious, place in recovery position and seek medical advice.  
Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable instruments/apparatus.

If inhaled

- : Administer oxygen if breathing is difficult or cyanosis is observed.  
Call a physician immediately.  
If breathed in, move person into fresh air.  
If not breathing, give artificial respiration.  
Contact a poison control center.  
Call a physician or poison control center immediately.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.

In case of skin contact

- : If symptoms persist, call a physician.  
In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash contaminated clothing before re-use.  
If on skin, rinse well with water.  
If on clothes, remove clothes.

In case of eye contact

- : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed

- : Call a physician immediately.  
Contact a poison control center.  
Rinse mouth thoroughly with water.  
Keep respiratory tract clear.  
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

- : May be fatal if swallowed and enters airways.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic if inhaled.  
sensitizing effects

Protection of first-aiders

- : First Aid responders should pay attention to self-protection and use the recommended protective clothing

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Notes to physician : Treat symptomatically and supportively.

## SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray jet  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Risk of explosion if heated under confinement.  
Possible emission of gaseous decomposition products may lead to a dangerous pressure build-up.  
Avoid confinement.  
Contact with incompatible materials or exposure to temperatures exceeding SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may auto-ignite.

The product burns violently.  
Flash back possible over considerable distance.  
Do not allow run-off from fire fighting to enter drains or water courses.  
Vapors may form explosive mixtures with air.  
The product will float on water and can be reignited on surface water.  
Cool closed containers exposed to fire with water spray.

Specific extinguishing methods : Do not use a solid water stream as it may scatter and spread fire.  
Remove undamaged containers from fire area if it is safe to do so.  
Use water spray to cool unopened containers.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use a water spray to cool fully closed containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice and personal protective equipment recommendations. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Never return spills in original containers for re-use. Treat recovered material as described in the section "Disposal considerations".

Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contact with incompatible substances can cause decomposition at or below SADT. Clear spills immediately. Suppress (knock down) gases/vapors/mists with a water spray jet. To clean the floor and all objects contaminated by this material, use plenty of water. Soak up with inert absorbent material. Isolate waste and do not reuse. Non-sparking tools should be used. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

---

## SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from heat and sources of ignition. Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Keep away from combustible material. Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure. Protect from contamination. Do not swallow. Do not breathe vapors/dust.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Avoid formation of aerosol.  
Take precautionary measures against static discharges.  
Never return any product to the container from which it was originally removed.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Avoid confinement.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash thoroughly after handling.  
For personal protection see section 8.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

|  |  |
|--|--|
| Conditions for safe storage              | :<br>Store in original container.<br>Keep containers tightly closed in a cool, well-ventilated place.<br>Store in cool place.<br>Contamination may result in dangerous pressure increases - closed containers may rupture.<br>Prevent unauthorized access.<br>Observe label precautions.<br>Store in accordance with the particular national regulations.<br>Avoid impurities (e.g. rust, dust, ash), risk of decomposition.<br>Electrical installations / working materials must comply with the technological safety standards.<br>Containers which are opened must be carefully resealed and kept upright to prevent leakage. |
| Materials to avoid                       | :<br>Keep away from combustible materials.<br>Keep away from strong acids, bases, heavy metal salts and other reducing substances.   |
| Recommended storage temperature          | : 14 - 104 °F<br>-10 - 40 °C   |
| Further information on storage stability | : Stable under recommended storage conditions.   |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

Version 2.1      Revision Date: 04/24/2024      SDS Number: 60000000061      Date of last issue: 03/27/2020  
Date of first issue: 04/03/2019

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components  | CAS-No.    | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis    |
|---|------------|-------------------------------|--|----------|
| Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9) | 64742-48-9 | TWA                           | 400 ppm<br>1,600 mg/m <sup>3</sup>             | OSHA P0  |
|   |            | TWA                           | 500 ppm<br>2,000 mg/m <sup>3</sup>             | OSHA Z-1 |

**Engineering measures** : Minimize workplace exposure concentrations.

#### Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an approved filter.

Filter type : ABEK-filter

Use NIOSH approved respiratory protection.

#### Hand protection

Material : Nitrile rubber  
Break through time : 480 min  
Glove thickness : 0.4 mm

Material : butyl-rubber  
Break through time : 10 min  
Glove thickness : 0.5 mm

#### Remarks

: The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work.  
For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

#### Eye protection

: Ensure that eyewash stations and safety showers are close to the workstation location.  
Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.  
Always wear eye protection when the potential for inadvertent

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

eye contact with the product cannot be excluded.

Tightly fitting safety goggles

Please wear suitable protective goggles. Also wear face protection if there is a splash hazard.

### Skin and body protection

: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Wear as appropriate:

Flame retardant antistatic protective clothing.

### Protective measures

: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### Hygiene measures

: Avoid contact with skin, eyes and clothing.  
Keep away from food and drink.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : pungent

pH : No data available

Melting point/range : < -20 °C

Boiling point/boiling range : Not applicable Decomposition

Flash point : 33 °C

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Method: closed cup

|  |   |  |
|--|---|--|
| Evaporation rate                                   | : | No data available  |
| Flammability (solid, gas)                          | : | Not applicable   |
| Self-ignition                                      | : | The substance or mixture is not classified as self heating. The substance or mixture is not classified as pyrophoric.  |
| Upper explosion limit / Upper flammability limit   | : | 6.2 % (V)<br>Solvent   |
| Lower explosion limit / Lower flammability limit   | : | 0.9 % (V)  |
| Vapor pressure                                     | : | 0.02 hPa (25 °C)   |
| Relative vapor density                             | : | No data available  |
| Density  | : | ca. 0.84 g/cm3 (20 °C)   |
| Solubility(ies)                                    |   |  |
| Water solubility                                   | : | negligible   |
| Partition coefficient: n-octanol/water             | : | log Pow: 1.6 (25 °C)   |
| Self-Accelerating decomposition temperature (SADT) | : | 70 °C<br>Method: UN-Test H.4<br>SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction. |
| Viscosity  |   |  |
| Viscosity, dynamic                                 | : | 1 mPa.s (20 °C)  |
| Explosive properties                               | : | Not explosive  |
| Oxidizing properties                               | : | The substance or mixture is not classified as oxidizing.<br>Organic peroxide   |

## SECTION 10. STABILITY AND REACTIVITY

|            |   |  |
|------------|---|--|
| Reactivity | : | Stable under recommended storage conditions. |
|------------|---|--|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Heating may cause a fire or explosion.

Chemical stability : Stable under recommended storage conditions.  
No decomposition if stored normally.

Possibility of hazardous reactions : Vapors may form explosive mixture with air.

Conditions to avoid : Protect from contamination.  
Contact with incompatible substances can cause decomposition at or below SADT.  
Heat, flames and sparks.  
Avoid confinement.

Incompatible materials : Accelerators, strong acids and bases, heavy metals and heavy metal salts, reducing agents

Hazardous decomposition products : Irritant, caustic, flammable, noxious/toxic gases and vapours can develop in the case of fire and decomposition

## SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Toxic if inhaled.

### Product:

Acute oral toxicity : LD50 (Rat, male): 3,195 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): 9.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit, male): 6,000 mg/kg  
Method: OECD Test Guideline 402

### Components:

#### **tert-butyl peracetate:**

Acute oral toxicity : LD50 (Rat, male): 1,597 mg/kg  
Method: OECD Test Guideline 401  
Remarks: The value is calculated

Acute inhalation toxicity : LC50 (Rat, male and female): 4.6 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Remarks: Calculation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Acute dermal toxicity : LD50 (Rabbit, male): 3,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: The value is calculated

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5000 ppm  
Exposure time: 8 h  
Test atmosphere: vapor  
Remarks: Insufficient Data to Classify  
Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

#### **Product:**

Result : No skin irritation

Remarks : May cause skin irritation in susceptible persons.

#### **Components:**

##### **tert-butyl peracetate:**

Species : Rabbit  
Result : No skin irritation

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Assessment : Repeated exposure may cause skin dryness or cracking.  
Result : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Species : Rabbit  
Result : Eye irritation  
Remarks : May cause irreversible eye damage.

#### **Components:**

##### **tert-butyl peracetate:**

Result : Eye irritation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

---

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Remarks : No eye irritation

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified due to lack of data.

#### Product:

Test Type : Maximization Test  
Result : May cause sensitization by skin contact.  
Remarks : Causes sensitization.

#### Components:

##### **tert-butyl peracetate:**

Test Type : Maximization Test  
Result : May cause sensitization by skin contact.

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Remarks : Did not cause sensitization on laboratory animals.

### Germ cell mutagenicity

Not classified due to lack of data.

#### Product:

Genotoxicity in vitro : Test Type: Ames test  
Result: mutagenic  
  
Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
  
Genotoxicity in vivo : Test Type: Micronucleus test  
Species: Mouse  
Method: OECD Test Guideline 474  
Result: negative

#### Components:

##### **tert-butyl peracetate:**

Genotoxicity in vitro : Test Type: Ames test

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Result: mutagenic

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test  
Species: Mouse  
Method: OECD Test Guideline 474  
Result: negative

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Germ cell mutagenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

Not classified due to lack of data.

### Components:

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified due to lack of data.

### Components:

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Effects on fetal development : Species: Rat  
Application Route: Oral  
Teratogenicity: NOAEL: 1,000  
Method: OECD Test Guideline 414  
Remarks: Based on data from similar materials

### STOT-single exposure

Not classified due to lack of data.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

### STOT-repeated exposure

Not classified due to lack of data.

### Repeated dose toxicity

#### Components:

##### **tert-butyl peracetate:**

|                   |   |                         |
|-------------------|---|-------------------------|
| Species           | : | Rat, male and female    |
| NOAEL             | : | 50 mg/kg                |
| Application Route | : | oral (gavage)           |
| Method            | : | OECD Test Guideline 422 |
| Remarks           | : | The value is calculated |
| Species           | : | Rat, male and female    |
| NOAEL             | : | 280 mg/kg               |
| Application Route | : | Inhalation              |
| Test atmosphere   | : | vapor                   |
| Exposure time     | : | 28                      |
| Method            | : | OECD Test Guideline 412 |
| Remarks           | : | The value is calculated |

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

|                   |   |                                      |
|-------------------|---|--------------------------------------|
| Species           | : | Rat                                  |
| NOAEL             | : | 1000 mg/kg                           |
| Application Route | : | 1,000 mg/kg                          |
| Exposure time     | : | Oral                                 |
| Remarks           | : | 4 wk                                 |
|                   |   | Based on data from similar materials |

### Aspiration toxicity

May be fatal if swallowed and enters airways.

#### Components:

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

May be fatal if swallowed and enters airways.

### Experience with human exposure

#### Components:

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

|              |   |  |
|--------------|---|--|
| Skin contact | : | Remarks: Prolonged skin contact may defat the skin and produce dermatitis. |
|--------------|---|--|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

### Further information

#### Product:

Remarks : Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **tert-butyl peracetate:**

|   |  |
|---|--|
| Toxicity to fish                                    | : LC50 (Danio rerio (zebra fish)): 39.6 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203   |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia magna (Water flea)): 4.31 mg/l<br>Exposure time: 48 h<br>Test Type: semi-static test<br>Method: OECD Test Guideline 202                    |
| Toxicity to algae/aquatic plants                    | : EC50 (Pseudokirchneriella subcapitata (green algae)): 6.4 mg/l<br>Exposure time: 72 h<br>Test Type: Growth inhibition<br>Method: OECD Test Guideline 201 |
|   | EC10 (Pseudokirchneriella subcapitata (green algae)): 2.6 mg/l<br>Exposure time: 72 h<br>Test Type: Growth inhibition<br>Method: OECD Test Guideline 201   |
| Toxicity to microorganisms                          | : EC50: 407.1 mg/l<br>Test Type: Respiration inhibition of activated sludge<br>Method: OECD Test Guideline 209   |

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

|   |   |
|---|---|
| Toxicity to fish                                    | : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l<br>Exposure time: 96 h           |
| Toxicity to daphnia and other aquatic invertebrates | : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l<br>Exposure time: 48 h                    |
| Toxicity to algae/aquatic plants                    | : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l<br>Exposure time: 72 h |

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): 316 mg/l  
Exposure time: 28 d

### Persistence and degradability

#### Components:

##### **tert-butyl peracetate:**

Biodegradability : Result: not rapidly degradable  
Method: Closed Bottle test

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Biodegradability : Result: Readily biodegradable.

### Bioaccumulative potential

#### Product:

Bioaccumulation : Bioconcentration factor (BCF): 5.28

#### Components:

##### **tert-butyl peracetate:**

Bioaccumulation : Bioconcentration factor (BCF): 5.28

Partition coefficient: n-octanol/water : log Pow: 1.6 (25 °C / 25 °C)

**Contains one or both isoparaffinic hydrocarbons (Naphtha hydrotreated heavy CAS 64742-48-9, Alkanes, C10-13-iso CAS 68551-19-9):**

Partition coefficient: n-octanol/water : Pow: > 4

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

mation unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility. The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Dispose of in accordance with local regulations. Clean container with water. Dispose of contents/ container to an approved waste disposal plant. Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 3103  
Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETATE)  
Class : 5.2  
Packing group : Not assigned by regulation  
Labels : 5.2  
Environmentally hazardous : yes

#### IATA-DGR

UN/ID No. : UN 3103  
Proper shipping name : Organic peroxide type C, liquid (tert-Butyl peroxyacetate)  
Class : 5.2  
Packing group : Not assigned by regulation  
Labels : Organic Peroxides, Keep Away From Heat  
Packing instruction (cargo aircraft) : 570  
Packing instruction (passenger aircraft) : 570

#### IMDG-Code

UN number : UN 3103  
Proper shipping name : ORGANIC PEROXIDE TYPE C, LIQUID (tert-BUTYL PEROXYACETATE)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

|                  |   |                            |
|------------------|---|----------------------------|
| Class            | : | 5.2                        |
| Packing group    | : | Not assigned by regulation |
| Labels           | : | 5.2                        |
| EmS Code         | : | F-J, S-R                   |
| Marine pollutant | : | yes                        |

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

|                      |   |  |
|----------------------|---|--|
| UN/ID/NA number      | : | UN 3103  |
| Proper shipping name | : | Organic peroxide type C, liquid<br>(tert-Butyl peroxyacetate, 50%) |
| Class                | : | 5.2  |
| Packing group        | : | Not assigned by regulation   |
| Labels               | : | ORGANIC PEROXIDE   |
| ERG Code             | : | 146  |
| Marine pollutant     | : | yes  |

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

|                      |   |  |
|----------------------|---|--|
| SARA 311/312 Hazards | : | Flammable (gases, aerosols, liquids, or solids)<br>Organic peroxides<br>Acute toxicity (any route of exposure)<br>Respiratory or skin sensitization<br>Aspiration hazard<br>Serious eye damage or eye irritation |
|----------------------|---|--|

|          |   |   |
|----------|---|---|
| SARA 313 | : | This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. |
|----------|---|---|

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMi Intermediate or Final VOC's (40 CFR 60.489).

### Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

### International Regulations

#### The ingredients of this product are reported in the following inventories:

|            |  |
|------------|--|
| TSCA (US)  | : All substances listed as active on the TSCA inventory  |
| AIIC (AU)  | : On the inventory, or in compliance with the inventory  |
| DSL (CA)   | : All components of this product are on the Canadian DSL |
| ENCS (JP)  | : On the inventory, or in compliance with the inventory  |
| ISHL (JP)  | : On the inventory, or in compliance with the inventory  |
| KECI (KR)  | : On the inventory, or in compliance with the inventory  |
| PICCS (PH) | : On the inventory, or in compliance with the inventory  |
| IECSC (CN) | : On the inventory, or in compliance with the inventory  |

### TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

---

## SECTION 16. OTHER INFORMATION

### Further information

This material safety datasheet only contains information relating to safety and does not replace any product information or product specification.

These safety instructions also apply to empty packaging which may still contain product residues. The hazards on the label also apply to residues in the container.

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 04/24/2024

### Full text of other abbreviations

|                |  |
|----------------|--|
| OSHA P0        | : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)               |
| OSHA Z-1       | : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA P0 / TWA  | : 8-hour time weighted average   |
| OSHA Z-1 / TWA | : 8-hour time weighted average   |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concern-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## TBPA-50-AL1

|                |                              |                            |   |
|----------------|------------------------------|----------------------------|---|
| Version<br>2.1 | Revision Date:<br>04/24/2024 | SDS Number:<br>60000000061 | Date of last issue: 03/27/2020<br>Date of first issue: 04/03/2019 |
|----------------|------------------------------|----------------------------|---|

ing the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8